

33 Stapleton Street  
Winnipeg, Manitoba, Canada, R2L 1Z9  
Toll Free U.S.A. & Canada **1-800-409-3484**

Ph. 204 988-3484  
Fax 204 988-3480

## ProTech – Finishing Filler

### Features:

- Easy to dispense and apply from 1:1 dual cartridges.
- Fast setting, 100% solids finishing filler.
- For both rigid and flexible plastics.
- Excellent adhesion to all commonly used plastics with proper preparation. (Refer to ProTech's P.R.I.M.E. tech sheet for plastic preparation instructions.)
- Easy sanding in 20 minutes to a fine feather-edge with no roll-up.
- Compatible with all primers and topcoats.
- 2 Year shelf life

### Packaging:

ProTech # EF452, EF462, EF482, EF492, EF882  
ProTech # EF456, EF466, EF486, EF496, EF886

### Technical Data:

Product	Rigid	Flex
Appearance	Part A black paste Part B white paste	Part A light blue paste Part B white paste
Mixing Ratio	1:1 by volume	1:1 by volume
% Wt. Solids	100%	100%
Work Time	7-9 min. (70°F, 21°C)	7-9 min. (70°F, 21°C)
Sanding Time	20 min. (70°F, 21°C)	20 min. (70°F, 21°C)
Paint Time	After sanding	After sanding

(Higher temperatures will decrease work and cure times. Heat may also be applied to speed up handling and cure.)