

MATERIAL SAFETY DATA SHEET

Accepted by O.S.H.A.

Complies with FORM OSHA-20.

1. COMPANY INFORMATION / PRODUCT IDENTIFICATION

Pro Technology International Ltd.
33 Stapleton Street Winnipeg, Manitoba
Canada, R2L 1Z9

Phone 1-204-988-3484
Fax 1-204-988-3480
email info@protechnology.com

Emergency Phone(s): **1-800-809-3484**

Product Name: **TEXTURE MOLDING COMPOUND PART B**
Product Part #: **Sample B**

2. HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

*n/a-not available

* n/e-not established

EXPOSURE LIMITS, PPM

COMPONENT	CAS #	OSHA		ACGIH	% MIX
		PEL(TWA)	TLV(TWA)	TLV(TWA)	
Inorganic Tin	301-10-0	n/a	2mg Sn/m ³		20-35%

NFPA RATINGS FOR THIS PRODUCT ARE: HEALTH 1, FLAMMABILITY 0, REACTIVITY 0

HMIS RATINGS FOR THIS PRODUCT ARE: HEALTH 1, FLAMMABILITY 0, REACTIVITY 0

3. PHYSICAL DATA

ODOR: Mild
COLOR(S): Clear
PHYSICAL STATE (@20 C): Liquid
VAPOR DENSITY (Air = 1) n/a
VAPOR PRESSURE: n/a
SPECIFIC GRAVITY: 1.262 +/- 0.050
EVAPORATION RATE : n/a
% VOLATILE B/V: None

4. FIRE & EXPLOSION HAZARD

FLAMMABILITY: Product is flammable as supplied.
FLASHPOINT: 142° C (288° F) - TCC
LEL/UEL: n/a / n/a
EXTINGUISHING MEDIA: Foam,Alcohol foam,CO₂,Dry chemical.
SPECIAL FIRE PRECAUTIONS: Water spray may be ineffective but may be used to cool containers exposed to heat.
Wear self-contained breathing apparatus.

MATERIAL SAFETY DATA SHEET

5. HEALTH HAZARD

ACUTE OVEREXPOSURE: Irritating to skin.
CHRONIC OVEREXPOSURE: Prolonged contact with skin can result in dermatitis and swelling. Swallowing can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air.
EYE CONTACT: Flush immediately with large volumes of water for at least 15 minutes. Consult a physician if irritation persists.
SKIN CONTACT: Remove with soap and water. Remove contaminated clothing.
INGESTION: DO NOT induce vomiting. Consult physician or poison control center immediately.

6. REACTIVITY DATA

STABILITY: Stable.
HAZARDOUS POLYMERIZATION: CANNOT occur.
CONDITIONS TO AVOID: Avoid elevated temperatures. Avoid contact with strong oxidizing agents.

7. SPILL OR LEAK PROCEDURES

SPILLS: Stop spill at source. Eliminate all ignition sources. Absorb liquid on paper or inert material (Floor Absorbant, sawdust, etc.) and pick up with shovel.
WASTE DISPOSAL METHODS: Place in closed containers. Do not close containers tightly as gassing may develop in some products. Carefully incinerate or use sanitary landfill in accordance with local and federal regulations.

8. SPECIAL PROTECTION INFORMATION

VENTILATION: Use local mechanical exhaust capable of minimizing vapor concentrations. Always use with adequate ventilation.
RESPIRATORY PROTECTION: Use NIOSH approved organic vapor cartridge or respirator designed to remove combination of particulates and vapor where concentrations are encountered.
EYE PROTECTION: Chemical safety goggles.
PROTECTIVE GLOVES: Neoprene or Nitrile rubber gloves.
OTHER: Impervious chemical safety apron and boots; eye wash.

9. SPECIAL PRECAUTIONS

STORAGE AND HANDLING: Wear rubber gloves and safety goggles while handling. Do not reuse empty container. Store in a cool, dry, well ventilated place. Keep containers tightly closed when not in use. Keep away from children and animals. Practice reasonable care and cleanliness.
OTHER: Avoid gross contamination of skin. Wash off skin with soap and water upon exposure.

MATERIAL SAFETY DATA SHEET

10. TOXICOLOGICAL INFORMATION

No toxicological information available.

11. ECOLOGICAL INFORMATION

No ecological information available.

12. TRANSPORT INFORMATION

CANADIAN TGD CLASSIFICATION: Flammable Class 3 UN 1133 Packing Group III

U.S. (DOT) REGULATIONS: Flammable Class 3 UN 1133 Packing Group III

13. REGULATORY INFORMATION

U.S. TSCA Inventory Status: All components of this product are either on the Toxic Substances Control Act (TSCA) Inventory List or exempt.

Canadian DSL Inventory Status: All components of this product are either on the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL) or exempt.

WHMIS Hazardous Classification: B2 Flammable Liquids, D2B Toxic Materials

14. OTHER INFORMATION

PREPARED BY: Pro Technology International Ltd., March 31, 2006.

VERSION: Texture Molding Compound Part B - 1

REVISIONS:

NOTICE:

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, PROTECHNOLOGY MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREFORE, PROTECHNOLOGY ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

BE SAFE:

READ OUR PRODUCT SAFETY INFORMATION AND PASS IT ON.